


## Bi-pin flat Led lamps

CODE: SERIE GU4

For replacing bi-pin halogen bulbs in spotlights with side connection.

18 white high brightness SMD 2835 LEDs

Power supply: 12V through a DC power supply or toroidal, ferromagnetic driver.



IP20 CRI 80

### Features

- Colour rendering: > 80
- Luminous efficiency: 112 lm/W
- Average life: 30,000 hours
- Protection degree: IP 20, for indoor use
- Dimensions: Ø 28x40 mm
- 

### Technical data

|                                                                                    | Article | Supply voltage | Dimensions  | Base | Total<br>consumption | Color              | Luminous flux | Angle of diffusion |
|------------------------------------------------------------------------------------|---------|----------------|-------------|------|----------------------|--------------------|---------------|--------------------|
|  | GU4.WW  | 12V            | ø28 x 40 mm | G 4  | 2,5W                 | warm white 3.000°K | 186 lm        | 360°               |
|  | GU4.D   | 12V            | ø28 x 40 mm | G 4  | 2,5W                 | day light 4.000°K  | 185 lm        | 360°               |
|  | GU4.W   | 12V            | ø28 x 40 mm | G 4  | 2,5W                 | cool white 6.000°K | 185 lm        | 360°               |



Traditional lamps and signalling products





# ENERG

## LYVIALED

### GU4.WW



**2**  
kWh/1000h



2019/2015



# ENERG

## LYVIALED

### GU4.D

---



---

**2**  
kWh/1000h



2019/2015



# ENERG

## LYVIALED

### GU4.W

---



---

**2**  
kWh/1000h



2019/2015