

## LOW CONSUMPTION STRIP

CODE: BLR.422

Professional led strip.

Due to the high heat output, the strip must be mounted on a material with good thermal dissipation (eg metal); we recommend our aluminum PA Series profiles.

Bag package comprising:

- 5 m reel
- 2 power cable



## Features

- 3528 SMD Led - 60 LED/m
- Selected bin colour
- Beam angle: 120°
- Minimum cutting section: 100 mm
- Extendible max: 5,000 mm
- Dimmable
- Colour rendering: >90
- Protection degree: IP20, for indoor use
- Working temperature: -25 +45°C
- Storage temperature: -20 +80°C
- Rear adhesive: 3M
- Material: copper 2 layer
- Substrate colour: white
- Average life: 36,000 hours
- Led operative life: L70B50




## Technical data

|  | Article    | Led colour    | Colour temp. | Volt   | Led type | Led/m | W/M | LM/M | LM/W | IP |
|--|------------|---------------|--------------|--------|----------|-------|-----|------|------|----|
|  | BLR.422.W  | Bianco Freddo | 6.500°K      | 24V DC | 3528 SMD | 60    | 4,8 | 384  | 80   | 20 |
|  | BLR.422.D  | Bianco Diurno | 4.000°K      | 24V DC | 3528 SMD | 60    | 4,8 | 384  | 80   | 20 |
|  | BLR.422.3W | Bianco Caldo  | 3.000°K      | 24V DC | 3528 SMD | 60    | 4,8 | 290  | 60   | 20 |
|  | BLR.422.G  | Giallo        |              | 24V DC | 3528 SMD | 60    | 4,8 | 60   | 12,5 | 20 |

## Accessori opzionali

|                            |                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ACCESSORIES FOR LED STRIPS | CONNETTORI RAPIDI, FLR.122.J, FLR.122.PC, FLR.180                                                                                                                                                                                                                                                                                                       |
| DRIVER AND DIMMER          | LB.700, LB.700.RF, NTG401, NTG400, VS3, RP2, SERIE CD, MD1, CTR2021, CTR1032, CTR2032, SLV401, OMN400, CTR217                                                                                                                                                                                                                                           |
| ALUMINUM PROFILES          | PA.251, PA.261, PA.262, PA.272, PA.241, PA.243, PA.244, PA.245, PA.252, PA.253, PA.275, PA.276, PA.285, PA.287, PA.282, PA.283, PA.288, PA.1806, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420, PA.510, PA.520, PA.530, PA.768, PA.769, PA.781, PA.790, PA.284, PA.289, PA.417, PA.233, PA.658 |

Data sheets





# ENERG

## LYVIALED

### BLR.422.W

---

A

B

C

D

E

F

G

G

---

**3**

kWh/1000h



2019/2015



# ENERG

## LYVIALED

### BLR.422.D

---

A

B

C

D

E

F

G

G

---

# 3

kWh/1000h



2019/2015



# ENERG

## LYVIALED

### BLR.422.3W

---

A

B

C

D

E

F

G

G

---

# 3

kWh/1000h



2019/2015