

HIGH BRIGHTNESS STRIP

CODE: BLR.160

Professional led strip.

Given the considerable heat production it is necessary to mount the strip on material with good heat dissipation (e.g. metal); we recommend our aluminium profiles.

Bag package comprising:

- 5 m reel
- 1 power cable

12V



IP20

CRI 90

COLORI VIVI



Features

- 2835 SMD Led - 60 LED/m
- Selected bin colour
- Beam angle: 120°
- Minimum cutting section: 50 mm
- Extendible max: 5,000 mm
- Dimmable
- Colour rendering: >90
- Protection degree: IP20, for indoor use


- Working temperature: -25 +65°C
- Storage temperature: -40 +80°C
- Rear adhesive: 3M
- Material: copper 2 layer
- Substrate colour: white
- Average life: 40,000 hours
- Led operative life: L80B20

Technical data

	Article	Led colour	Colour temp.	Volt	Led type	Led/m	W/M	LM/M	LM/W	IP
	BLR.160.W	Bianco Freddo	6500°K	12V DC	2835 SMD	60	14,4	1320	91	20
	BLR.160.D	Bianco Diurno	4000°K	12V DC	2835 SMD	60	14,4	1300	90	20
	BLR.160.3W	Bianco Caldo	3000°K	12V DC	2835 SMD	60	14,4	1290	89	20
	BLR.160.XW	Bianco Extra Caldo	2700°K	12V DC	2835 SMD	60	14,4	1280	88	20

Accessori opzionali

ACCESSORIES FOR LED STRIPS	CONNETTORI RAPIDI, FLR.160.PC
DRIVER AND DIMMER	LB.700, LB.700.RF, NTG401, NTG400, VS3, RP2, SERIE CD, MD1, CTR2021, CTR1032, CTR2032, SLV401, OMN400, CTR217
ALUMINUM PROFILES	PA.251, PA.261, PA.262, PA.272, PA.241, PA.243, PA.244, PA.245, PA.252, PA.253, PA.275, PA.276, PA.285, PA.287, PA.282, PA.283, PA.288, PA.1806, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420, PA.510, PA.520, PA.530, PA.768, PA.769, PA.781, PA.790, PA.284, PA.289, PA.417, PA.233, PA.658





ENERG

LYVIALED

BLR.160.W

A

B

C

D

E

F

G

G

2

kWh/1000h



2019/2015



ENERG

LYVIALED

BLR.160.D

A

B

C

D

E

F

G

G

2

kWh/1000h



2019/2015



ENERG

LYVIALED

BLR.160.3W



2
kWh/1000h



2019/2015



ENERG

LYVIALED

BLR.160.XW

A

B

C

D

E

F

G

G

2

kWh/1000h



2019/2015