

Led round ceiling lamp

CODE: MOON

Round ceiling lamps with LED technology.
The essential design and "minimal" lines allow a very wide use of these ceiling lamps, which can be installed on the ceiling or wall.
Round ceiling lamps with integrated plate with high luminous LEDs for a uniform diffusion of light on the entire surface.
White techno-polymer body with high mechanical resistance.
High diffusion satin diffuser in polycarbonate.
Equipped with rear bracket for wall mounting.
Complete with terminals for electrical connections

IP44 CRI 80

Features

- Power supply: 230V ~ 50Hz
- Colour rendering: >80
- Luminous efficiency: 90 lm/W
- Power factor: >0.7
- Average life: 30,000 hours
- Operating temperature: -20°C +40°C
- Insulation class: II
- Beam angle: 120°
- Protection degree: IP44, for outdoor use
- Shockproof: IK10

Technical data

Article	Dimensions	Total consumption	Protection degree	Color	Luminous flux	Angle of diffusion
MN12.D	Ø230x56 mm	15 W	IP44	day light 4.000°K	1.250 lm	120°
MN12.WW	Ø230x56 mm	15 W	IP44	warm white 3.000°K	1.250 lm	120°
MN15.D	Ø280x62 mm	20 W	IP44	day light 4.000°K	1.650 lm	120°
MN15.WW	Ø280x62 mm	20 W	IP44	warm white 3.000°K	1.650 lm	120°
MN20.D	Ø330x68 mm	24 W	IP44	day light 4.000°K	2.250 lm.	120°
MN20.WW	Ø330x68 mm	24 W	IP44	warm white 3.000°K	2.250 lm	120°



Cabinets and recessed



Data sheets

