

WATERPROOF HIGH DENSITY STRIP

CODE: FLR.714

Professional led strip.

Transparent silicone sheath shockproof.

Due to the high heat output, the strip must be mounted on a material with good thermal dissipation (eg metal); we recommend our aluminum PA Series profiles.

Bag package comprising:

- 5 m reels
- 1 power cable
- 10 clips with screws

24V



IP66

CRI 90 - TYP 94

COLORI VIVI



Features

- 3014 SMD Led - 140 LED/m
- Selected bin colour
- Beam angle: 120°
- Minimum cutting section: 100 mm
- Extendible max: 5,000 mm
- Dimmable
- Colour rendering: >90 - TYP 94
- Protection degree: IP66, for outdoor use
- Working temperature: -20 +45°C
- Storage temperature: 0 +60°C
- Rear adhesive: 3M - 9080A
- Material: copper/polyamide 3 layer
- Substrate colour: white
- Average life: 65,000 hours @T45°C
- Led operative life: L70B10

Technical data

Article	Led colour	Colour temp.	Volt	Led type	Led/m	W/M	LM/M	LM/W	IP
FLR.714.D	Bianco Diurno	4.000°K	24V DC	3014 SMD	140	12,6	1.500	119	66
FLR.714.WW	Bianco Caldo	3.000°K	24V DC	3014 SMD	140	12,6	1.450	115	66
FLR.714.XW	Bianco Extra Caldo	2.700°K	24V DC	3014 SMD	140	12,6	1.580	125	66

Accessori opzionali

ACCESSORIES FOR LED STRIPS	FLR.125.KIT
DRIVER AND DIMMER	LB.430, LB.700, LB.700.RF, SERIE SLB, NTG401, NTG400, VS3, RP2, MD1, CTR2021, CTR1032, CTR2032, SLV401, OMN400, CTR217
ALUMINUM PROFILES	PA.251, PA.261, PA.262, PA.272, PA.241, PA.243, PA.244, PA.245, PA.252, PA.253, PA.275, PA.276, PA.285, PA.287, PA.282, PA.283, PA.288, PA.1806, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420, PA.510, PA.520, PA.530, PA.768, PA.769, PA.781, PA.790, PA.284, PA.289, PA.417, PA.233, PA.658



Data sheets

