

HIGH LIGHT OUTPUT / LOW CONSUMPTION STRIP

CODE: FLR.765

Professional led strip.

Transparent silicone sheath, walkable, impact resistant.

Due to the high heat output, the strip must be mounted on a material with good thermal dissipation (eg metal); we recommend our aluminum PA Series profiles.

Bag package comprising:

- 5m reels
- 1 power cord



Features

- 2835 SMD Led - 128 LED/m
- Selected bin colour
- Beam angle: 120°
- Minimum cutting section: 62.5 mm
- Extendible max: 5,000 mm
- Dimmable
- Colour rendering: >90
- Protection degree: IP67, for outdoor use
- Working temperature: -25 +45°C
- Storage temperature: 0 +60°C
- Rear adhesive: 3M
- Material: copper/polyamide 2 layer
- Substrate colour: white
- Average life: 30.000 hours @T55°C
- Led operative life: L70B20

Technical data

Article	Led colour	Colour temp.	Volt	Led type	Led/m	W/M	LM/M	LM/W	IP
FLR.765.D	Bianco Diurno	4000°K	24V DC	2835 SMD	128	6,5	944	145	67
FLR.765.3W	Bianco Caldo	3000°K	24V DC	2835 SMD	128	6,5	912	140	67
FLR.765.XW	Bianco Extra Caldo	2700°K	24V DC	2835 SMD	128	6,5	890	137	67

Accessori opzionali

ACCESSORIES FOR LED STRIPS	FLR.125.KIT
DRIVER AND DIMMER	LB.430, LB.700, LB.700.RF, SERIE SLB, NTG401, NTG400, VS3, RP2, MD1, CTR2021, CTR1032, CTR2032, SLV401, OMN400, CTR217
ALUMINUM PROFILES	PA.241, PA.244, PA.245, PA.253, PA.275, PA.276, PA.287, PA.282, PA.283, PA.288, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420, PA.510, PA.520, PA.530, PA.781, PA.289, PA.417, PA.233, PA.658



Data sheets

