



LED spot light

CODE: TITAN 30W

- Body in powder-coated die-cast aluminium
- LED: Array Bridgelux patented
- Anti-glare reflector, high-efficiency, maximises light output
- Silver reflector to optimise the flux
- Mounting bracket with bearing scale

A++

IP65

Features

- Operating voltage: 110V - 230V~
- Frequency: 50Hz-60Hz
- Working voltage: DC30-36V
- IP 65 waterproof driver
- Connection terminals
- LED: COB
- Colour rendering: >75
- Energy efficiency: >82%
- LED luminous efficiency: 90lm/W
- Luminous efficiency: >85%
- Power factor: >0.98
- LED life: 50000 hours
- Operating temperature: -40°C +55°C
- Protection degree: IP65

Technical data

Article	Dimensions	Body color	Total consumption	Color	Luminous flux	Angle of diffusion	Weight
SP.201	315x245x80 mm	grey	30 W	white 5.500°K	2.700 lm	120°	3 kg
SP.201.D	315x245x80 mm	grey	30 W	day light 4.000°K	2.500 lm	120°	3 kg
SP.201.WW	315x245x80 mm	grey	30 W	warm white 2.700°K	2.400 lm	120°	3 kg
SP.301	315x245x80 mm	white	30 W	day light 4.000°K	2.500 lm	120°	3 kg
SP.101	315x245x80 mm	white	30 W	warm white 2.700°K	2.400 lm	120°	3 kg



Appliance for outdoor



Data sheets

