



DIGITAL STRIP

CODE: FLR.520

This LED strip can carry up to 132 different lighting effects, thanks to its special construction and its controller.

The particular flexibility, the ability to cut every 6 cm approx. and its small dimensions make it ideal for decorative and/or security lighting in cinema, entertainment, hotels, bars, museums and public places.

Very easily you can change color and effect, so even changing the atmosphere of the place where the strip is installed.

Ideal for decoration light of indoor and outdoor.

Bag package comprising:

- 5 m reel
- 2 power cables

To supply each strip or piece of it you need:

- n. 1 controller. art. FLR.530
- n. 1 power supply art. FLR.532
- n. 1 pair cables art. FLR.533

Because of the large production of heat is necessary to fit the strip of material with good heat dissipation (metal); recommend our aluminum profiles.







Features

- 5050 SMD Led 48 LED/m
- Beam angle: 100°
- Minimum cutting section: 62.5 mm
- Extendible max: 5,000 mm
- Dimmable
- Protection degree: IP20, for indoor use

- Working temperature: -20 +45°C
- Storage temperature: -20 +60°C
- Rear adhesive: 3M
- Material: copper 2 layer
- Substrate colour: white
- Average life: 30,000 hours

Technical data

Article	Led colour	Volt	Led type	Led/m	W/M	IP
FLR.520	MULTICOLOR	12V DC	5050 SMD	48	11,52	20

Accessori opzionali

ACCESSORIES FOR LED STRIPS	FLR.533
DRIVER AND DIMMER	FLR.530, FLR.532
ALUMINUM PROFILES	PA.251, PA.261, PA.262, PA.272, PA.241, PA.243, PA.244, PA.245, PA.252, PA.253, PA.275, PA.276, PA.285, PA.287, PA.282, PA.283, PA.288,
	PA.1806, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420, PA.510, PA.520, PA.530,
	PA.768, PA.769, PA.781, PA.790, PA.284, PA.289, PA.417, PA.233, PA.658





Data sheets

