



LED mini cabinet lamp

CODE: BRITELITE PLUS

Use the latest SMD LEDs that with equal absorption ensure a higher luminous flux. With an aluminium profile with a standard section of 30x22 mm (H x D) 5 different models are developed.

First advantage: low power for high light yields, therefore excellent efficiency and energy savings.

Second advantage: thanks to the small size of the "heads" you can directly connect a ceiling lamp with another without need separate connectors; long "bright strips" are obtained, without need to individually power each ceiling lamp.

Complete with power cord, connecting cable and clip for wall fixing.

IP20 CRI 80

Features

- Low consumption
- High light yield
- Light on the entire length
- Body in white painted aluminium
- Diffuser in polycarbonate
- Extendable, for direct connection up to 120W
- ON/OFF switch on the body
- Power supply: 230V - 50 Hz
- Protection degree: IP20, for indoor use
- Colour rendering: >80
- Operating temperature: -20°C +50°C
- Average life: 25,000 hours

Technical data

Article	Supply voltage	Dimensions	Total consumption	Protection degree	Color	Luminous flux	Angle of diffusion
BR05.WW	230V - 50 Hz	22x30x313 mm	5W	IP20	warm white 3.000°K	500 lm	180°
BR05.D	230V - 50 Hz	22x30x313 mm	5W	IP20	day light 4.000°K	525 lm	180°
BR05.W	230V - 50 Hz	22x30x313 mm	5W	IP20	cool white 6.000°K	550 lm	180°
BR08.WW	230V - 50 Hz	22x30x543 mm	10W	IP20	warm white 3.000°K	1000 lm	180°
BR08.D	230V - 50 Hz	22x30x543 mm	10W	IP20	day light 4.000°K	1050 lm	180°
BR08.W	230V - 50 Hz	22x30x543 mm	10W	IP20	cool white 6.000°K	1100 lm	180°
BR13.WW	230V - 50 Hz	22x30x873 mm	13W	IP20	warm white 3.000°K	1300 lm	180°
BR13.D	230V - 50 Hz	22x30x873 mm	13W	IP20	day light 4.000°K	1365 lm	180°
BR13.W	230V - 50 Hz	22x30x873 mm	13W	IP20	cool white 6.000°K	1400 lm	180°
BR19.WW	230V - 50 Hz	22x30x1.173	20W	IP20	warm white 3.000°K	2000 lm	180°
BR19.D	230V - 50 Hz	22x30x1.173	20W	IP20	day light 4.000°K	2100 lm	180°
BR19.W	230V - 50 Hz	22x30x1.173	20W	IP20	cool white 6.000°K	2200 lm	180°
BR21.WW	230V - 50 Hz	22x30x1.473	24W	IP20	warm white 3.000°K	2400 lm	180°
BR21.D	230V - 50 Hz	22x30x1.473	24W	IP20	day light 4.000°K	2550 lm	180°
BR21.W	230V - 50 Hz	22x30x1.473	24W	IP20	cool white 6.000°K	2600 lm	180°



Cabinets and recessed

