

LED spot light

CODE: TITAN 240W

- Body in powder-coated die-cast aluminium
- LED: Array Bridgelux patented
- Anti-glare reflector, high-efficiency, maximises light output
- Silver reflector to optimise the flux
- Mounting bracket with bearing scale

A++

IP65



Features

- Operating voltage: 85V - 265V~
- Frequency: 50Hz-60Hz
- Working voltage: DC12-24V
- IP 65 waterproof driver
- Connection terminals
- LED: 4 pcs COB
- Colour rendering: >75
- Energy efficiency: >82%
- LED luminous efficiency: 90lm/W
- Luminous efficiency: >90%
- Power factor: >0.95
- LED life: 50000 hours
- Operating temperature: -40°C +55°C
- Protection degree: IP65

Technical data

Article	Dimensions	Body color	Total consumption	Color	Luminous flux	Angle of diffusion	Weight
SP.205	425x485x140 mm	grey	240 W	white 5.500°K	21.600 lm	120°	14 kg
SP.205.D	425x485x140 mm	grey	240 W	day light 4.000°K	21.000 lm	120°	14 kg
SP.205.WW	425x485x140 mm	grey	240 W	warm white 2.700°K	20.000 lm	120°	14 kg
SP.105	425x485x140 mm	white	240 W	warm white 2.700°K	20.000 lm	120°	14 kg



Appliance for outdoor



Data sheets

