



## High bay

CODE: JUPITER 100W

- Lamp body in die-cast aluminum, black colour, with rear finings for heat dissipation
- Led SMD Lumileds
- Polycarbonate protection lens
- Waterproof driver Meanwell

A++



IP65

CRI 80

## Features

- Power supply: 100-277V
- Frequency: 50-60Hz
- Dimmable: 0-10V
- Colour temperature: 4000°K
- Colour rendering: >80
- Luminous efficiency: 140 lm/W
- Power factor: >0,9
- Working Temperature: -20°C +50°C
- Protection degree: IP65 for outdoor use
- Led operating life: L70B10 @ 142.000 hours
- Average life: 50,000 hours
- Insulation class: I
- Equipped with power cord: 3x0,75mm2 H05RN-F
- Shockproof: IK06

## Technical data

| Article    | Dimensions  | Total consumption | Color             | Luminous flux | Angle of diffusion | Weight |
|------------|-------------|-------------------|-------------------|---------------|--------------------|--------|
| JP100.D    | Ø340x180 mm | 100W              | day light 4.000°K | 14.000 lm     | 90°                | 3,9 kg |
| JP100.D50  | Ø340x180 mm | 100W              | day light 4.000°K | 14.000 lm     | 60°                | 3,9 kg |
| JP100.D120 | Ø340x180 mm | 100W              | day light 4.000°K | 14.000 lm     | 120°               | 3,9 kg |

## Accessori opzionali

|               |                          |
|---------------|--------------------------|
| HIGHBAY LED   | JPG2, JPC, JPF, JPB, JPM |
| LED PROJECTOR | FLAC1                    |



Appliance for outdoor



Data sheets

