

Magnetic led circline

CODE: CIRCOLED

Also ideal for backlighting displays and/or light walls.
Magnetic led circline for replacement in the old round ceiling lights.
Aluminium base with transparent polycarbonate diffuser.
Equipped with magnets on the back for easy installation.
Provided with holes for fixing with screws.
Terminal block on board for connection.
Built-in power supply for perfect LED management. Magnetic led circline for fluorescent circline replacement in the old ceiling lights.
Aluminium body with transparent polycarbonate diffuser.
Equipped with rear magnets for easy installation.
Terminal block on board, for connection









IP20 CRI 80

Features


- Power supply: 220-240 V - 50/60 Hz
- Color rendering index: >80
- Average life: 25,000 hours
- Insulation class: II
- Protection rating: IP20, for indoor use

Technical data

	Article	Dimensions	Total consumption	Protection degree	Color	Luminous flux	Angle of diffusion	Weight
	CLM12.D	Ø166x28 mm	12 W	IP20	day light 4.000°K	1000 lm	120°	300 gr
	CLM12.WW	Ø166x28 mm	12 W	IP20	warm white 3.000°K	900 lm	120°	300 gr
	CLM16.D	Ø220x28 mm	16 W	IP20	day light 4.000°K	1300 lm	120°	500 gr
	CLM16.WW	Ø220x28 mm	16 W	IP20	warm white 3.000°K	1200 lm	120°	500 gr
	CLM24.D	Ø288x28 mm	24 W	IP20	day light 4.000°K	2000 lm	120°	600 gr
	CLM24.WW	Ø288x28 mm	24 W	IP20	warm white 3.000°K	1900 lm	120°	600 gr



Data sheets





ENERG

LYVIALED

CLM12.D



12
kWh/1000h



2019/2015



ENERG

LYVIALED

CLM12.WW



12
kWh/1000h



2019/2015



ENERG

LYVIALED

CLM16.D



16

kWh/1000h



2019/2015



ENERG

LYVIALED

CLM16.WW



16
kWh/1000h



2019/2015



ENERG

LYVIALED

CLM24.D



24
kWh/1000h



2019/2015



ENERG

LYVIALED

CLM24.WW



24
kWh/1000h



2019/2015