



Led squared ceiling lamp 3 in 1

CODE: TRITONQ SMART

Innovative squared ceiling lamps with LED technology.
Equipped with presence detector and battery.

3 selectable functions:

- Colour change (3000 - 4000 - 5700°K).
- Automatic light on with presence detector.
- Automatic intervention in case of blackout.

The essential design and "minimal" lines allow a very wide use of these ceiling lamps, which can be installed on the ceiling or wall.

Plate with high luminous LEDs for a uniform diffusion of light on the entire surface.

White polycarbonate body with high mechanical resistance.

High diffusion satin diffuser in polycarbonate.

"No Flicker" IC integrated driver.

Equipped with rear bracket for wall mounting.

Junction box for electrical connections.

Change colour selector.

IP54 CRI 80

Features

- Power supply: 230V ~ 50Hz
- Colour rendering: >80
- Luminous efficiency: 100 lm/W
- Power factor: >0.5
- Timer: 15 sec - 5 min
- Twilight: from 15 to 200 lux
- Adjustment of detected area: 1 - 7 m (default: 2m)
- Ni.cd buffer battery
- Average charging time: 12 hours
- Average intervention time: 1 sec
- Flux in emergency: 200 lm
- Autonomy: 1 hour
- Average life: 30,000 hours
- Operating temperature: -20°C + +40°C
- Insulation class: II
- Beam angle: 120°
- Protection degree: IP54, for outdoor use
- Shockproof: IK08
- Photo-biological safety: RG 0

Technical data

Article	Dimensions	Total consumption	Protection degree	Color	Luminous flux	Angle of diffusion
TQS28	280 x 280 x 50 mm	18 W	IP54	3000-4000-5700°K	2.100 lm	120°
TQS33	330 x 330 x 50 mm	24 W	IP54	3000-4000-5700°K	2.900 lm	120°



Cabinets and recessed



Data sheets

