



Led squared ceiling lamp 3 in 1

CODE: TRITONQ SMART

Square ceiling light with LED technology. Equipped with presence detector and buffer battery. Four selectable functions:

- Change of tone (3000 4000 5700°K).
- Automatic switch-on via presence detector.
- Emergency intervention in the event of a blackout.

The essential design and "minimal" lines allow for a very wide use of this ceiling light, which can be installed both on the ceiling and on the wall.

The plate with high-luminance LEDs guarantees uniform diffusion of light over the entire surface. Thanks to the optional remote control art. TLC, it is possible to select/adjust the many functions these ceiling lights are equipped with. Body in white polycarbonate with high mechanical resistance.

Satin diffuser in polycarbonate with high light diffusion.

Integrated IC "no flicker" power supply.

Equipped with a rear bracket for wall mounting and steel cable to facilitate installation and leave your hands free for electrical connections.

Terminal block for electrical connection with watertight seal.

NEW STAND-BY FUNCTION: The ceiling light turns on as a permanent courtesy light, only - and until - the ambient light level is lower than the selected one. When it detects passage, it switches to 100% light for the set time.



Features

- Satin diffuser in polycarbonate with high light diffusion
- Body in white polycarbonate with high mechanical resistance
- Power supply: 230V-50Hz
- Colour rendering: >80
- Power factor: >0.5
- Beam opening: 120°
- Average life: 30,000

Insulation class: II

- Operating temperature: -20 +40°C
- IP65 for outdoor use
- Impact resistant: IK08
- Photobiological safety: RG 0
- Ni.cd buffer battery

Technical data

Article	Dimensions	Total	Protection degree	Color	Luminous flux	Angle of diffusion	Weight
		consumption					
TQS28	280 x 280 x 50 mm	18 W	IP65	3000-4000-5700°K	2.100 lm	120°	770 gr
TQS33	330 x 330 x 50 mm	24 W	IP65	3000-4000-5700°K	2.900 lm	120°	1015 gr

Data sheets

