Arteleta International S.p.A.
Via Pellizza da Volpedo 57 - 20092 Cinisello Balsamo (MI) - ITALY
Tel: +39.02.66013541 - Fax: +39.02.6122573



Asymmetrycal LED spot light

CODE: FOBOS 200W

VERY HIGH LUMINOUS EFFICIENCY 130 LM/W

- Body in black power-coated die-cast aluminium, good corrosion resistance
- LED: LUMILEDS 3030
- Asymmetric beam angle 65° x 120°
- Anti-glare reflector, high-efficiency, maximises light output
- Tempered glass
- Mounting bracket with stainless steel screws

A++ IP65 CRI 80


Features


- Operating voltage: 100V - 277V
- Frequency: 50Hz - 60HZ
- Waterproof driver Meanwell
- Colour rendering: >80
- LED luminous efficiency: 130 lm/W
- Power factor: >0.95
- Average life: 50,000 hours
- Led operating life: L70B10 @ 152.000 hours
- Operating temperature: - 20°C +50°C
- Protection degree: IP65, for outdoor use
- Shock proof: IK08
- With rubber power cord H05RN-F 3 x 1mm² L=30 cm, with IP65 waterproof connector (item FLAC1)

Technical data

Article	Dimensions	Body color	Total consumption	Color	Luminous flux	Angle of diffusion	Weight
FO20040	364x434x58 mm	black	200 W	day light 4.000°K	26.000 lm	65°x120°	7,58 kg
FO20057	364x434x58 mm	black	200 W	cool white 5.700°K	27.300 lm	65°x120°	7,58 kg

Data sheets





L1	L2	L3	Ø1	Ø2
140.0	180.0	220.0	13	15

dimensioni in mm

Appliance for outdoor