

WATERPROOF HIGH DENSITY STRIP

CODE: FLR.721

NO DOTS EFFECT

Professional use led strip.

Transparent silicone sheath shockproof.

Due to the high heat output, the strip must be mounted on a material with good thermal dissipation (eg metal); we recommend our aluminum PA Series profiles.

Bag package comprising:

- 5 m reels
- 1 power cord
- 10 clips with screws

24V



IP66

CRI 90 - TYP 94

COLORI VIVI



Features

- 3014 SMD Led - 210 LED/m
- Selected bin colour
- Beam angle: 120°
- Minimum cutting section: 66.6 mm
- Extendible max: 5,000 mm
- Dimmable
- Colour rendering: >90 - TYP 94
- Protection degree: IP66, for outdoor use

- Working temperature: -20 +45°C
- Storage temperature: 0 +60°C
- Rear adhesive: 3M - 9080A
- Material: copper/polyamide 3 layer
- Substrate colour: white
- Average life: 65,000 hours @T45°C
- Led operative life: L70B10

Technical data

Article	Led colour	Colour temp.	Volt	Led type	Led/m	W/M	LM/M	LM/W	IP
FLR.721.D	Bianco Diurno	4000°K	24V DC	3014 SMD	210	17	2.300	135	66

ACCESSORIES FOR LED FLR.125.KIT

STRIPS

DRIVER AND DIMMER LB.430, LB.700, LB.700.RF, SERIE SLB, NTG401, NTG400, VS3, RP2, MD1, CTR2021, CTR1032, CTR2032, SLV401, OMN400, CTR217

ALUMINUM PROFILES PA.272, PA.241, PA.253, PA.275, PA.276, PA.285, PA.287, PA.282, PA.283, PA.288, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420, PA.510, PA.520, PA.530, PA.768, PA.769, PA.781, PA.790, PA.284, PA.289, PA.417, PA.233, PA.658



Data sheets

