

LED FLOODLIGHT WITH SEPARATE SOLAR PANEL

CODE: TWP14

LED spotlight separated from the solar panel, to allow installation even in non-sunny environments.

Equipped with presence detector and twilight sensor to allow automatic intervention.

IP65



Features

- Connection cable between panel and lighthouse: length 5m
- LED headlight equipped with optics with lenses
- LED Type: SMD 2835
- Beam opening: 120°
- Color rendering: > 80
- Very high capacity lithium battery type LifePO4 6.4V 18,000mAh (replaceable)
- Charging time: 6 hours
- Autonomy (with fully charged battery): 15 hours
- Equipped with remote control to allow setting of brightness, intervention time and 3 different programs.
- Detection angle: 140° x 70°
- Detection distance: 8 m
- Twilight sensor: intervention < 20 lux
- Easy wall installation via adjustable bracket
- Degree of protection: IP65, for outdoor use
- Weatherproof and UV-resistant die-cast aluminum body
- Solar panel: monocrystalline
- Average life: 50,000 hours
- Operating temperature: -15 +70°C
- Insulation class: II
- Operating cycles: >30,000
- Remote control range: 8 m

Technical data

Article	Dimensions	Total consumption	Color	Luminous flux	Weight
TWP14	375x275x56 mm (faro) - 350x600x20 mm (pannello)	13,5W	day light 4.000°K	1680 lm	5 kg (faro) - 1,8 kg (pannello)



Appliance for outdoor

