

LED FLOODLIGHT WITH SEPARATE SOLAR PANEL

CODE: TWP19

LED headlight separated from the solar panel, allows installation even in non-sunny environments.

Equipped with presence detector and twilight sensor to allow automatic intervention.

IP65



Features

- Connection cable between panel and lighthouse: length 5m
- LED headlight equipped with optics with lenses
- LED Type: 192xSMD 2835
- Beam opening: 120°
- Color rendering: > 80
- Very high capacity lithium battery type LifePO4 6.4V 24000mAh (replaceable)
- Charging time: 6 hours
- Autonomy (with fully charged battery): 15 hours
- Equipped with remote control to allow setting of brightness, intervention time and 2 different programs:
 - A) Upon detection 100% light for 30 sec. 1 light off
 - B) Upon detection 100% light for 30 sec. 30% light
- Detection angle: 140° x 70°
- Detection distance: 8 m
- Twilight sensor: intervention < 20 lux
- Easy wall installation via adjustable bracket

Technical data

Article	Dimensions	Total consumption	Color	Luminous flux	Weight
TWP19	375x275x56 mm (faro) - 400x600x20 mm (pannello)	18W	day light 4.000°K	2280 lm	6 kg (faro) - 2,55 kg (pannello)



Appliance for outdoor

