Arteleta International S.p.A.
Via Pellizza da Volpedo 57 - 20092 Cinisello Balsamo (MI) - ITALY
Tel: +39.02.66013541 - Fax: +39.02.6122573



WALL LAMP

CODE: **SJR1**

Equipped with presence detector and twilight sensor to allow automatic intervention.

LED Type: 40 x SMD 2835

Color rendering: > 80

Lithium battery: 3.7V - 2200 mAh type 18650

Charging time: 8 hours

Autonomy (with fully charged battery): 16 hours

3 different programs:

A) Courtesy light always on at 12%

B) Upon detection ? 65% light for 25 sec. ? light at 12%

C) Upon detection ? 100% light for 25 sec. ? light off

Equipped with a passive infrared presence sensor incorporated into the lighthouse

Detection angle: 90°

Detection distance: 8 m

Twilight sensor: intervention < 50 lux

Degree of protection: IP44, for outdoor use

Stainless steel body resistant to weather, UV rays and impacts

Polycarbonate diffuser

Solar panel: monocrystalline 1.8W 6V

Average life: 25,000 hours

Operating temperature: -20 +40°C

Insulation class: III

Operating cycles: >12,500

IP44

Technical data

Article	Dimensions	Total consumption	Color	Luminous flux	Weight
SJR1	Ø 178 x 185 x 220 mm	6W	day light 4.000°K	600 lm	0,69 kg

Appliance for outdoor