



LOW BOLLARD

CODE: SJR45

Ideal for 360° lighting.

Complete with stainless steel stem.

Equipped with presence detector and twilight sensor to allow automatic intervention.

IP44

Features

- LED Type: 40 x SMD 2835
- Color rendering: > 80
- Lithium battery: 3.7V - 2200 mAh type 18650 (replaceable)
- Charging time: 8 hours
- Autonomy (with fully charged battery): 16 hours
- 3 different programs:
 - A) Courtesy light always on at 12%
 - B) Upon detection 65% light for 25 sec. light at 12%
 - C) Upon detection 100% light for 25 sec. light off
- Detection angle: 90°
- Detection distance: 8 m
- Twilight sensor: intervention < 50 lux
- Degree of protection: IP44, for outdoor use
- Stainless steel body resistant to weather, UV rays and impacts
- Polycarbonate diffuser
- Solar panel: monocrystalline 1.8W 6V
- Average life: 25,000 hours
- Operating temperature: -20 +40°C
- Insulation class: III
- Operating cycles: >12,500

Technical data

Article	Dimensions	Total consumption	Color	Luminous flux	Weight
SJR45	Ø 178 x 450 mm	6W	day light 4.000°K	600 lm	0,76 kg



Appliance for outdoor

