

LED FLOODLIGHT WITH SEPARATE SOLAR PANEL

CODE: TWP200

Equipped with a twilight sensor to allow automatic intervention.
LED spotlight separated from the solar panel, to allow installation even in non-sunny environments.

IP65



Features

- Connection cable between panel and lighthouse: 3m length
- LED Type: 180 x SMD 2835
- Beam opening: 90°
- Color rendering: > 80
- Very high capacity lithium battery 3.7V – 25,000 mAh (non-replaceable)
- Charging time: 5 hours
- Autonomy (with fully charged battery): 15 hours
- Equipped with remote control to allow setting of brightness and intervention time
- Twilight sensor: intervention < 20 lux
- Easy wall installation via adjustable bracket
- Degree of protection: IP65, for outdoor use
- Weatherproof, UV and impact resistant die-cast aluminum body IK08
- Solar panel: 6V monocrystalline
- Average life: 50,000 hours
- Operating temperature: -20 +55°C
- Insulation class: II
- Operating cycles: > 20,000

Technical data

Article	Dimensions	Total consumption	Color	Luminous flux	Weight
TWP200	330x250x30 (faro) 300x390x17 (pannello)	10,5W	day light 4.000°K	1900 lm	1,9 kg (faro) - 1,2 kg (pannello)



Appliance for outdoor

