

HIGH DENSITY LED STRIP

CODE: **FLR.372**

The package includes:
reel 5m
power cord



Features

- LED type SMD 2835 - 240 LED/m
- Selected color bin
- Beam angle: 120°
- Minimum cutting section: 33 mm
- Max. extendable: 5,000 mm
- Dimmable
- Color rendering index: >80
- Protection degree: IP20, for indoor use
- Operating temp.: -20 +45°C
- Storage temp.: 0 +60°C
- Rear adhesive: 3M
- Material: 3-layer polyamide
- Support color: white
- Average life: 50,000 hours
- Operating life: L70B50

Technical data

	Article	Led colour	Colour temp.	Volt	Led type	Led/m	W/M	LM/M	LM/W	IP
	FLR.372.D	bianco diurno	4000°K	24V	SMD2835	240	12,6	2100	166	20
	FLR.372.3W	bianco caldo	3000°K	24V	SMD2835	240	12,6	2000	158	20
ACCESSORIES FOR LED STRIPS		FLR.160.PC								
DRIVER AND DIMMER		LB.700, LB.700.RF, NTG401, NTG400, VS3, RP2, MD1, NTG500, CTR2021, CTR1032, CTR2032, SLV401, OMN400, CTR217, DAD4M, DAD1								
ALUMINUM PROFILES		PA.251, PA.261, PA.262, PA.272, PA.241, PA.243, PA.253, PA.275, PA.276, PA.285, PA.287, PA.282, PA.283, PA.288, PA.1806, PA.221, PA.222, PA.351, PA.310, PA.362, PA.452, PA.416, PA.430, PA.440, PA.450, PA.460, PA.410, PA.420								



ENERG

LYVIALED

FLR.372.D



13
kWh/1000h



2019/2015



ENERG

LYVIALED

FLR.372.3W



13
kWh/1000h



2019/2015