

## LED projectors changing shades of white

### CODE: CHANGE EVOLUTION



Symmetrical optics  
Equipped with a color temperature selector: 3,000 - 4,000 - 5,700°K  
Operating voltage: 220V - 240V - 50Hz  
Color rendering index: >80  
LED luminous efficacy: 110 lm/W  
Power factor: >0.9  
LED operating life: L80B10  
Average life (\*): 40,000 hours  
Operating temperature: -25°C +45°C  
IP65 protection rating, for outdoor use  
Impact resistance: IK08  
Die-cast aluminum body  
Scratch-resistant finish black  
Excellent corrosion resistance  
High-efficiency reflector, to maximize light output  
Anti-glare tempered glass  
Driver with DOB technology  
Equipped with an adjustable wall mounting bracket 360°  
Power compartment with on-board terminal block

**IP65** CRI 80

### Technical data

Article	Dimensions	Body color	Total consumption	Color	Luminous flux	Angle of diffusion	Weight
<b>XC10E</b>	120x127x44 mm	black	10W	3000-4000-5700°K	1100 lm	120°	0,330 kg
<b>XC20E</b>	166x180x46 mm	black	20W	3000-4000-5700°K	2200 lm	120°	0,500 kg
<b>XC30E</b>	197x200x46 mm	black	30W	3000-4000-5700°K	3300 lm	120°	0,750 kg
<b>XC50E</b>	222x230x47 mm	black	50W	3000-4000-5700°K	5500 lm	120°	0,975 kg
LED PROJECTOR		XCN					



Appliance for outdoor

