Arteleta International S.p.A.
Via Pellizza da Volpedo 57 - 20092 Cinisello Balsamo (MI) - ITALY
Tel: +39.02.66013541 - Fax: +39.02.6122573



LED projectors changing shades of white

CODE: **CHANGE EVOLUTION**

Symmetrical optics
Equipped with a color temperature selector: 3,000 - 4,000 - 5,700°K
Operating voltage: 220V - 240V - 50Hz
Color rendering index: >80
LED luminous efficacy: 110 lm/W
Power factor: >0.9
LED operating life: L80B10
Average life (*): 40,000 hours
Operating temperature: -25°C +45°C
IP65 protection rating, for outdoor use
Impact resistance: IK08
Die-cast aluminum body
Scratch-resistant finish black
Excellent corrosion resistance
High-efficiency reflector, to maximize light output
Anti-glare tempered glass
Driver with DOB technology
Equipped with an adjustable wall mounting bracket 360°
Power compartment with on-board terminal block

IP65 CRI 80

Technical data

Article	Dimensions	Body color	Total consumption	Color	Luminous flux	Angle of diffusion	Weight
XC10E	120x127x44 mm	black	10W	3000-4000-5700°K	1100 lm	120°	0,330 kg
XC20E	166x180x46 mm	black	20W	3000-4000-5700°K	2200 lm	120°	0,500 kg
XC30E	197x200x46 mm	black	30W	3000-4000-5700°K	3300 lm	120°	0,750 kg
XC50E	222x230x47 mm	black	50W	3000-4000-5700°K	5500 lm	120°	0,975 kg

LED PROJECTOR XCN